

SUPERSEDING ASSY NO	SUPERSEDES	VOLTS	LAMP No	MOUNTING TYPE	PWR TERM STUD SIZE	STR RLF STUD SIZE	EXT CORD LGTH	REVISIONS					
								LTR.	DESCRIPTION	DATE	DR	CHKD.	APVD
15-0007-23	30235		LESS LAMP	STRAIGHT	#10	#10	50"	AA	REDRAWN	3-19-73	RB	RB	
-1	30235-3/3	28	3/3				50"	AB	ADDED NOTE	6-23-82	MS	FK	ADP
-25	-1-3/3	28	3/3				36"						
-27	-2-3/3	28	3/3				72"						
-29	-18/6	13	18/6				50"						
-31	-3/6	6	3/6				50"						
-23	-3		LESS LAMP				50"						
-23	-3-3/3	28	3/3				50"						
-25	-5		LESS LAMP				36"						
-25	30235-5-3/3	28	3/3	STRAIGHT	#10	#10	36"						

NOTE: 30235 TYPES ARE SUPERSEDED
BY AN IMPROVED DESIGN 15-0007

FOR MANUFACTURING DETAILS
SEE DWG 15-0007

FOR PROCUREMENT USE EQUIVALENT
15-0007-() SUPERSEDING NUMBER

Ⓐ RUBBER STAMP NUMBER "30235-() ON
NAMEPLATE, PER GRIMES SPEC. S5-33063, CLASS 2

				FIND ITEM	CODE IDENT	PART NO.	NOMENCLATURE	STOCK SIZE	MATERIAL	FINISH	STK CODE
QTY. REQD.				PARTS LIST							
NOTICE "This drawing embodies a proprietary design originated by Grimes Manufacturing Company and shall not be disclosed, used, or duplicated for procurement or manufacturing purposes, unless specifically authorized by the Grimes Manufacturing Company. All patent rights relating hereto are expressly reserved for Grimes Manufacturing Company." This notice shall be marked on any reproduction hereof in whole or in part.				RIVET PER GRIMES SPEC S5 33002		TOLERANCES EXCEPT AS NOTED: LINEAR .XX ± .03 XXX ± .010 ANGULAR ± 0° 30'		DFTSMN BRUNOTTE 3-19-73		GRIMES MANUFACTURING COMPANY URBANA, OHIO	
				INSTALL THREADED FASTENERS PER GRIMES SPEC S5-33018				CHKD BRUNOTTE 3-19-73			
				SURFACES ROUGHNESS PER MIL-STD-10 (GRIMES SPEC S5-33017)		MATL SPEC		APVD		COCKPIT UTILITY LT SPOT & FLOOD (RED & WHITE)	
				✓		FINISH SPEC		APVD D Cx 5-30-73			
								RLSE G. WARD 5-30-73			
PT NO	NEXT ASSY.	END ITEM	QTY.					SIZE B	CODE IDENT. NO. 72914	30235	
APPLICATION								SCALE	WT.	SH OF 1	